

UNIQ[®] FLOW 386 S

Version 3.6 EU

Revision Date: 2020.12.12 Print Date: 2020.12.12

1. Identification of the substance/mixture and of the company/undertaking

UNIQ[®] FLOW 386 S

Use: industrial chemicals

Manufacturer: UNIQCHEM SHANGHAI CO., LTD.Address: 1809 Qixin Road, West Zone, Building 8Room 2308, Red Dot City, Minhang District, 201101Shanghai, ChinaEmergency information:Emergency number:Tel: +86 21 5433 6481

2. Hazards Identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3, H226: Flammable liquid and vapour.
Serious eye injury / eye irritation, Category 2A, H319: Causes serious eye irritation. **2.2 Label elements**

Labelling (REGULATION (EC) No 1272/2008) Hazard pictograms:



Signal word: Warning

Hazard statements:

H226: Flammable liquid and vapour.

H319: Causes serious eye irritation.

Precautionary statements:

Prevention:

P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical/ventilating/light/.../equipment.

P260: Do not breathe dust/ fume/ gas/ mist/vapours/ spray.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P303 + P361 + P353: IF ON SKIN (or hair), Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.



UNIQ[®] FLOW 386 S

Version 3.6 EU

Revision Date: 2020.12.12 Print Date: 2020.12.12

P304+P340: IF INHALED, remove victim to fresh air and keep at rest in a position.

P312: CALL a POISON CENTER or doctor/physician if you feel unwell.

P332 + P313: If skin irritation occurs: Get medical advice/attention.

P370 + P378: In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage:

P403+P235: Store in a well-ventilated place. Keep cool.

P405: Store locked up.

Disposal:

P501: Dispose of contents/container in accordance with national, state and local regulations.

3. Composition/Information on Ingredients

3.1 Mixtures

Chemical nature: Solution of modified acrylic polymer

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration
		(REGULATION (EC) No	[%]
		1272/2008)	
1-Methoxy-2-propyl acetate	108-65-6	H226 H319	≥40-≤50

For explanation of abbreviations see section 16.

4. First-Aid Measures

4.1 Description of first aid measures

General advice:

Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended.

If inhaled:

If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.

In case of skin contact:

If skin irritation persists, call a physician.

If on skin, rinse well with water.

If on clothes, remove clothes.

In case of eye contact:

Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Protect unharmed eye.

Keep eye wide open while rinsing.



UNIQ[®] FLOW 386 S

Version 3.6 EU

Revision Date: 2020.12.12 Print Date: 2020.12.12

If eye irritation persists, consult a specialist. **If swallowed:** Keep respiratory tract clear. Do not induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

- 4.2 Most important symptoms and effects, both acute and delayed Symptoms: No information available.Risks: No information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** Treatment: No information available.

5. Fire-Fighting Measures

5.1 Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam Carbon dioxide (CO₂) Dry chemical Unsuitable extinguishing media: High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting: Do not allow run-off from fire-fighting to enter drains or water courses.

Hazardous combustion products: Carbon oxides

5.3 Advice for firefighters

Special protective equipment

Wear self-contained breathing apparatus for firefighting, for firefighters if necessary.

Further information:

Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions:

Use personal protective equipment.

Ensure adequate ventilation.



UNIQ[®] FLOW 386 S

Version 3.6 EU

Revision Date: 2020.12.12 Print Date: 2020.12.12

Remove all sources of ignition.

Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions:

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up:

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For disposal considerations see section 13, For personal protection see section 8.

7. Handling and Storage

7.1 Precautions for safe handling

Advice on safe handling:

Avoid formation of aerosol.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes.

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the application area.

Take precautionary measures against static discharges.

Provide sufficient air exchange and/or exhaust in work rooms.

Open drum carefully as content may be under pressure.

Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion:

Do not spray on a naked flame or any incandescent material.

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).

Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures:

When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities Requirements for storage areas and containers:



UNIQ[®] FLOW 386 S

Version 3.6 EU

Keep container tightly closed in a dry and well-ventilated place.

Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with the technological safety standards. **Advice on common storage:**

No materials to be especially mentioned

7.3 Specific end use(s)

Specific use(s): No data available

8. Exposure Controls/Personal Protection

8.1 Control parameters:

Components	CAS-No.	Туре	Control parameters	
			Value	Value
			(ppm)	(mg/m ³)
1-Methoxy-2-propyl	108-65-6	TWA	50	275
acetate		STEL	100	550

8.2 Exposure controls

Personal protective equipment

Hand protection:

Material: 4H

Break through time: 240 min

Glove thickness: 0.7 mm

Remarks: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection:

Eye wash bottle with pure water

Tightly fitting safety goggles

Skin and body protection:

Impervious clothing.

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection:

In the case of vapour formation, use a respirator with an approved filter.

Environmental exposure controls

General advice:

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform respective authorities.



UNIQ[®] FLOW 386 S

Version 3.6 EU

Revision Date: 2020.12.12 Print Date: 2020.12.12

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance:	Liquid
Color:	Clear Colorless
Odor:	Slight, characteristic
pH:	No data available
Flash point:	45 °C, Method: 48 (Abel-Pensky)
Ignition temperature:	315°C
Initial boiling point:	146°C
Upper explosion limit:	10.8 %(V)
Lower explosion limit:	1.0 %(V)
Density:	1.0 g/cm ³ (20 °C)
Bulk density:	Not applicable
Solubility(ies)	
Water solubility:	Immiscible
Solubility in other solvents:	No data available
Viscosity (Viscosity, kinematic):	No data available

9.2 Other information

Surface tension:

No data available

10. Stability and Reactivity

10.1 Reactivity

Stable at normal ambient temperature and pressure.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions:

No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid: Heat, flames, sparks and strong oxidant.

10.5 Incompatible materials

Materials to avoid: No data available.

10.6 Hazardous decomposition products

Oxycarbide

11. Toxicological Information

11.1 Information on toxicological effects Acute toxicity



UNIQ [®] FLOW	/ 386 S
------------------------	---------

Version 3.6 EU

Revision Date: 2020.12.12 Print Date: 2020.12.12

Acute oral toxicity: No data available Acute inhalation toxicity: No data available Acute dermal toxicity: No data available Aspiration hazard No data available Skin corrosion/irritation No data available Serious eye damage/eye irritation Causes serious eye irritation Sensitization, skin or respiratory No data available Target Organ Systemic Toxicant - Single exposure No data available **Target Organ Systemic Toxicant - Repeated exposure** No data available Germ cell mutagenicity No data available **Reproductive toxicity** No data available Effects on foetal development No data available Repeated dose toxicity No data available

12. Ecological Information

12.1 Toxicity

Toxicity to fish: No data available

12.2 Persistence and degradability

Biodegradability: No data available

12.3 Bioaccumulative potential

Bioaccumulation: No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.



UNIQ[®] FLOW 386 S

Version 3.6 EU

Revision Date: 2020.12.12 Print Date: 2020.12.12

12.6 Other adverse effects

Additional ecological information: No data available

13. Disposal Considerations

13.1 Waste treatment methods

Product:

The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.

Contaminated packaging:

Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

Land transport ADR / RID	:
Class:	3
Packaging group:	III
UN number:	1993
ADR/RID-Labels:	3
Description of the goods:	FLAMMABLE LIQUID, N.O.S. (1-Methoxy-2-propyl acetate)
Sea transport IMDG:	
Class:	3
Packaging group:	III
UN number:	1993
IMDG-Labels:	3
EmS number:	F-E, S-E
Description of the goods:	FLAMMABLE LIQUID, N.O.S. (1-Methoxy-2-propyl acetate)
Marine pollutant:	No
Air transport IATA-DGR :	
Class:	3
Packaging group:	III
UN number:	1993
IATA-DGR-Labels:	3
Description of the goods:	FLAMMABLE LIQUID, N.O.S. (1-Methoxy-2-propyl acetate)



UNIQ[®] FLOW 386 S

Version 3.6 EU

Revision Date: 2020.12.12 Print Date: 2020.12.12

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Inventory of Existing Chemical Substances in China (IECSC): All components are listed or exempted.

European Inventory of Existing Commercial Chemical Substances (EINECS) & European List of Notified Chemical Substances (ELINCS): All components are listed or exempted.

Switzerland List of Toxic Substances (Giftliste 1) & Switzerland Inventory of Notified New Substances (INNS):): All components are listed or exempted.

Toxic Substance Control Act (TSCA): All components are listed or exempted.

Canada Domestic Substances List (DSL) & Canada Non-Domestic Substances List (NDSL): All components are listed or exempted.

Australia Inventory of Chemical Substances (AICS): All components are listed or exempted.

New Zealand Inventory of Chemicals (NZIoC): All components are listed or exempted.

Japan Chemical Substance Control Law (CSCL) & Japan Industrial Safety and Health Law (ISHL): All components are listed or exempted.

Korean Existing Chemicals List (KECL): All components are listed or exempted.

Philippines Inventory of Chemicals and Chemical Substances (PICCS): All components are listed or exempted.

Taiwan Chemical Substances Inventory(TCSI): All components are listed or exempted.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII): Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59): This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

Seveso II - Directive 2003/105/EC amending Council Directive 96/82/EC on the control of major accident hazards involving dangerous substances: Not applicable

15.2 Chemical Safety Assessment

Not applicable

16. Other Information

The information contained herein is based on the present state of our knowledge and does therefore not guarantee certain properties.