Printing date 04.04.2023 Version number 1 Revision: 13.01.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Methyl ethyl ketone

· Article number: 159 · CAS Number: 78-93-3

· EC number: 201-159-0

· Index number: 606-002-00-3

· Registration number 01-2119457290-43

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU8 Manufacture of bulk, large scale chemicals (including petroleum products)

SU9 Manufacture of fine chemicals

SU10 Formulation [mixing] of preparations and/or re-packaging (excluding alloys)

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Process category

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition

PROC4 Chemical production where opportunity for exposure arises

PROC5 Mixing or blending in batch processes

PROC6 Calendering operations PROC7 Industrial spraying

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC10 Roller application or brushing

PROC11 Non industrial spraying

PROC13 Treatment of articles by dipping and pouring

PROC14 Tabletting, compression, extrusion, pelletisation, granulation

PROC15 Use as laboratory reagent

PROC16 Use of fuels

PROC17 Lubrication at high energy conditions in metal working operations

PROC18 General greasing /lubrication at high kinetic energy conditions

PROC19 Manual activities involving hand contact

PROC21 Low energy manipulation and handling of substances bound in/on materials or articles

· Application of the substance / the mixture Solvent for various applications

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Möller Chemie GmbH & Co. KG

Bürgerkamp 1 D-48565 Steinfurt Tel.: 02551/9340-0

Fax: 02551/9340-60

· Further information obtainable from: Product safety department

· 1.4 Emergency telephone number:

Poison Control Center Mainz - 24 hour emergency service - Tel.: +49 (0) 6131/19240

Printing date 04.04.2023 Version number 1 Revision: 13.01.2023

Trade name: Methyl ethyl ketone

(Contd. of page 1)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The substance is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- · Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P241 *Use explosion-proof [electrical/ventilating/lighting] equipment.*

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

· 2.3 Other hazards

The product does not contain any substance above the legal limits included on the list for endocrine disrupting properties established under Article 59(1) of Regulation (EC) No 1907/2006 or under Commission Delegated Regulation (EU) 2017/2100 or of Commission Regulation (EU) 2018/605 has endocrine disrupting properties.

· Results of PBT and vPvB assessment

· *PBT*:

The product does not contain any substances above legal limits that meet the criteria for PBT (persistent, bioaccumulative and toxic).

The product does not contain any substances above legal limits that meet the criteria for vPvB (very persistent and very bioaccumulative).

Printing date 04.04.2023 Version number 1 Revision: 13.01.2023

Trade name: Methyl ethyl ketone

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

· 3.1 Substances

· CAS No. Description

78-93-3 methyl ethyl ketone

· Identification number(s)

· EC number: 201-159-0

· Index number: 606-002-00-3

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air, consult doctor in case of complaints.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fire with alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture Carbon monoxide
- · 5.3 Advice for firefighters
- · Protective equipment: Wear fully protective suit.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomaceous earth, acid binder, universal binder, sawdust). Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Keep container tightly closed in a well-ventilated place. Use of local and general ventilation. Keep cool. Protect from sun exposure.

(Contd. on page 4)

Printing date 04.04.2023 Version number 1 Revision: 13.01.2023

Trade name: Methyl ethyl ketone

(Contd. of page 3)

- · Information about storage in one common storage facility: Store away from oxidising agents.
- · Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.
- · Storage class:

3

flammable

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

78-93-3 butanone

IOELV Short-term value: 900 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm

· DNELs

worker:

Long-term exposure - systemic effects, dermal:1161 mg/kg Long-term exposure - systemic effects, inhalative: 600 mg/m³

Consumer:

Long-term exposure - systemic effects, dermal: 412 mg/kg Long-term exposure - systemic effects, oral: 31 mg/kg Long-term exposure - systemic effects, inhalative: 106 mg/m³

· PNECs

Fresh water: 55.8 mg/l Sea water: 55.8 mg/l

intermittent release: 55.8 mg/l Sewage treatment plant: 709 mg/l

Soil: 22.5 mg/kg

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

· Body protection: flame retardant antistatic protective clothing

Printing date 04.04.2023 Version number 1 Revision: 13.01.2023

Trade name: Methyl ethyl ketone

(Contd. of page 4)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical at	na cnemicai	properues
--	-------------	-----------

· General Information

· Colour: Colourless · Odour: Characteristic • Melting point/freezing point: -86 °C

· Boiling point or initial boiling point and boiling

79-80.5 °C

· Lower and upper explosion limit

1.8 Vol % · Lower: · Upper: 11.5 Vol % · Flash point: -9 °C · Ignition temperature: 514 °C

· Viscosity:

Dynamic at 15 °C: 0.423 mPas

·Solubility

· water at 20 °C: 250 g/l · Vapour pressure at 20 °C: 105 hPa

Density and/or relative density

Density at 20 °C: $0.804-0.807 \text{ g/cm}^3$

· 9.2 Other information

· Appearance:

Fluid · Form:

· Important information on protection of health and environment, and on safety.

· Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

Information with regard to physical hazard classes

Void · Explosives · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void · Flammable liquids

Highly flammable liquid and vapour.

· Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void Self-heating substances and mixtures Void

· Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void · Desensitised explosives Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity With proper handling and storage, no dangerous reactions occur.
- · 10.2 Chemical stability

The product is stable if the regulations / instructions for storage and handling are observed.

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions Reacts with strong oxidising agents.

(Contd. on page 6)

Printing date 04.04.2023 Version number 1 Revision: 13.01.2023

Trade name: Methyl ethyl ketone

(Contd. of page 5)

- · 10.4 Conditions to avoid Avoid all sources of ignition: heat, sparks, open flames.
- · 10.5 Incompatible materials: Strong oxidizing agents
- · 10.6 Hazardous decomposition products:

Thermal decomposition is highly dependent on the external conditions. It forms a complex mixture of liquid and gases in the air, including carbon monoxide and carbon dioxide and other organic compounds, when this material undergoes combustion or thermal or oxidative degradation.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

Dermal LD50 >2.000 mg/kg (rat)

- · Skin corrosion/irritation Slight irritant effect possible does not require labeling.
- · Serious eye damage/irritation

Causes serious eye irritation.

- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:

The product does not contain any substance above the legal limits included on the list for endocrine disrupting properties established under Article 59(1) of Regulation (EC) No 1907/2006 or under Commission Delegated Regulation (EU) 2017/2100 or of Commission Regulation (EU) 2018/605 has endocrine disrupting properties.

- · 11.2 Information on other hazards
- · Endocrine disrupting properties Substance is not listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

LC50796 h: 2993 mg/l (Pimephales promelas)

EC50748 h: 308 mg/l (Daphnia magna)

EC50/96 h: 2029 mg/l (Pseudokirchneriella subcapitata)

- · 12.2 Persistence and degradability Easily biodegradable
- · 12.3 Bioaccumulative potential Keine wesentliche Bioakkumulation
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: This substance is not considered to be persistent, bioaccumulating nor toxic (PBT).
- **vPvB**: This substance is not considered to be very persistent nor very bioaccumulative (vPvB).
- · 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Assessment by list): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Printing date 04.04.2023 Version number 1 Revision: 13.01.2023

Trade name: Methyl ethyl ketone

(Contd. of page 6)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- $\cdot \textit{Recommendation Disposal according to local regulations}.$
- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number ADR, IMDG, IATA	UN1193
14.2 UN proper shipping name ADR	1193 ETHYL METHYL KETONE (METHYL ETHY KETONE)
IMDG, IATA	ETHYL METHYL KETONE (METHYL ETHY KETONE)
14.3 Transport hazard class(es)	
ADR	
Class	3 (F1) Flammable liquids.
Label IMDG, IATA	3
Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR, IMDG, IATA	II
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code): EMS Number:	33 F-E,S-D
Stowage Category	B B
14.7 Maritime transport in bulk according to IM instruments	I O Not applicable.
Transport/Additional information:	пот присполе.
ADR	
Limited quantities (LQ)	IL
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	D/E

Printing date 04.04.2023 Version number 1 Revision: 13.01.2023

Trade name: Methyl ethyl ketone

(Contd. of page 7)

· IMDG	
· Limited quantities (LQ)	IL
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1193 ETHYL METHYL KETONE (METHYL ETHYL
	KETONE). 3. II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 40
- · DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

Substance is not listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

Substance is not listed.

- · Annex II REPORTABLE EXPLOSIVES PRECURSORS Substance is not listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: Mrs. Steyer
- Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3